

1050

Plastic Magic Adhesion Promoter

Plastic Magic works like magic in preventing paint peeling on new unfinished plastic parts and previously painted surfaces even without sanding.

Benefits:

- Prevents paint peeling on new unfinished plastic parts and previously painted surfaces.
- No need to identify plastic. Plastic Magic works on all plastics.
- Easy to use. Just spray on and allow to flash off.
- Plastic Magic can be top coated with any type paint system.

Application:

- Clean first with soap and water to remove water soluble contaminants.
- Clean with Super Clean plastic cleaner (Part no. 1000) to remove mold release agents and other contaminants.
- Apply on medium wet coat of Plastic Magic and allow to flash off at least 2-3 minutes, then follow with a full wet coat and allow to dry at least 15 minutes before color coating.
- It is important to allow the 15 minutes cure time in order for the chemicals to bite into the plastic or painted surface.



- Gallon and quart sizes may be poured into a spray bottle, into a spray gun, or poured straight from the container. Aerosol can is ready to use.

1050 Plastic Magic Adhesion Promoter

Dimensions: **1050-1**, 1 U.S. Gallon F-Style (3.785 liters)
6.5 in width x 4.1 in depth x 10.3 in height
(16.5cm x 10.4cm x 26.2cm)

1050-4, 1 U.S. Quart F-Style (946 ml)
4.5 in width x 2.5 in. depth x 7.4 in. height
(11.7cm x 6.1cm x 18.8)

1050-A, 19 fl. oz. (562 ml)
9.5 in height x 2.7 in diameter
24 cm x 7 cm

Weight: **1050-1** 7.15 lb (3.2 kg)

1050-4 2.06 lb (0.93 kg)

1050-A 1.20 lb (0.54 kg)