

3000

Light Gray Flexible Primer-Surfacer

3000 Light Gray Flexible Primer-Surfacer is a high-build, easy sanding undercoat for flexible plastics, SMC, fiberglass, or metal.

Benefits:

- High build formulation hides 180 grit sandscratches with ease.
- Single-stage fast drying acrylic lacquer formulation allows for quick sanding.
- Sands like chalk -- doesn't load the sandpaper even when dry sanding.
- Light gray color allows for easy hiding by any color topcoat. May be topcoated with any type of paint system.
- Flexible -- will not crack when bent 60 degrees over a 1-1/2 inch radius.

Application:

- Clean the plastic prior to repair and refinishing with 1000 Super Clean Plastic Cleaner.
- Spray any raw plastic areas to be primed with 1050 Plastic Magic adhesion promoter.
- Stir 3000 Flexible Primer Surfacer thoroughly and thin up to 10% with a good quality acrylic lacquer thinner if desired. Using 30 - 50 psi at the gun, apply two or three very light coats allowing 2 - 3 minutes of flash time between coats. Allow final coat to dry at least 30 minutes before sanding.



3000 Light Gray Flexible Primer Surfacer

Dimensions:	3000-1 , 1 U.S. Gallon F-Style (3.785 liters) 6.5 in width x 4.1 in depth x 10.3 in height (16.5cm x 10.4cm x 26.2cm)
	3000-4 , 1 U.S. Quart (946 ml) 4.3 in diameter x 4.9 in height (10.9cm diameter x 12.4cm height)
	3000-A , 13 oz. aerosol (370 grams) 2.6 in diameter x 7.8 in height (6.6cm diameter x 19.8cm height)
Weight:	3000-1 10.6 lb (4.8 kg)
	3000-4 2.7 lb (1.2 kg)
	3000-A 1.0 lb (0.5 kg)